

MAHLE

Driven by performance

AXLE JACKS



This series of jacks is known throughout the industry as the most reliable and longest lasting lift system of its kind. Their compact and field-ready design and low starting height makes them ideal for shop use or road service work.

www.servicesolutions.mahle.com

ShopPRO®

Axle Jack

Four hydraulic axle jack options, three with a 25 ton capacity, and one at a 35 ton capacity.

FEATURES:

- Unique QuickLift® feature, internal design raises the ram to the load at a quicker rate of speed
- Low starting height of 8" allows for easy positioning and spotting underneath low profile vehicles
- Patent pending air ram retract feature allows the user to reset the ram back to minimum starting height without reconnecting the hose
- Short handled version ideal for road service work

ADDITIONAL FEATURES

Black Armor Coating™ Protects the ram from rust and corrosion to extend longevity of product

Anti-Corrosive System The distinctive design of the internal system protects the hydraulic system to extend product life



485 80051 00	CAJ-25 25 Ton Axle Jack
485 80053 00	CAJ-25LP 25 Ton Axle Jack – Large Pad
485 80052 00	CAJ-25S 25 Ton Axle Jack – Short Handle
485 80054 00	CAJ-35 35 Ton Axle Jack

FEATURE COMPARISON

	CAJ-25	CAJ-25LP	CAJ-25S	CAJ-35
Capacity	50,000 lb (22,680 kg)	50,000 lb (22,680 kg)	50,000 lb (22,680 kg)	70,000 lb (31,751 kg)
Minimum Start Height	8 in (20 cm)	-	8 in (20 cm)	-
Maximum Lift Height	21 in (53 cm)	-	21 in (53 cm)	-
Power Source	Air/Hydraulic	-	Air/Hydraulic	-
Required Air Pressure	90 to 120 psi (6.2 to 8.3 bar)	-	90 to 120 psi (6.2 to 8.3 bar)	110 to 200 psi (7.7 to 13.8 bar)
Stroke	5.1 in (13 cm)	5.1 in (13 cm)	5.1 in (13 cm)	5.1 in (13 cm)
Extension Screw Adjustment	4.9 in (12 cm)	-	4.9 in (12 cm)	-
Frame Width	12 in (30 cm)	-	12 in (30 cm)	-
Frame Length	20 in (51 cm)	-	20 in (51 cm)	-
Wheel Diameter	8 in (20 cm)	-	8 in (20 cm)	-
Handle Length	53 in (135 cm)	-	23 in (58 cm)	-
Shipping Weight	124 lb (56 kg)	120 lb (54 kg)	124 lb (56 kg)	146 lb (66 kg)
Maximum Air Pressure	-	200 psi (13.8 bar)	-	-
Starting Height (SH)	-	8.7 in (22 cm)	-	-
SH w/ Short Lift Pad Extension	-	11 in (28 cm)	-	-
SH w/ Tall Lift Pad Extension	-	13.7 in (35 cm)	-	-
SH w/ Short and Tall Lift Pad Extensions	-	16 in (41 cm)	-	-
Lifting Height (LH)	-	13.6 in (35 cm)	-	-
LH w/ Short Lift Pad Extension	-	16.2 in (41 cm)	-	-
LH w/ Tall Lift Pad Extension	-	18.8 in (48 cm)	-	-
LH w/ Short and Tall Lift Pad Extensions	-	21.1 in (54 cm)	-	-
Lift Pad Diameter	-	3.5 in (9 cm)	-	-
Lift Pad Start Height	-	-	-	9.3 in (24 cm)
Lift Pad Start Height w/ Adapter	-	-	-	11.9 in (30 cm)
Screw Adjustment	-	-	-	5 in (13 cm)
Length (Handle Horizontal)	-	-	-	71 in (180 cm)
Width at Wheels	-	-	-	14.3 in (36 cm)
Overall Height (Handle Vertical)	-	-	-	58.5 in (149 cm)